

Saab 9³ 2003+ Armrest Powerport

Dealer Installation Instructions

These instructions are intended to be given to your Saab Service Technician.

If you would like to install this yourself, please visit us on the web at www.etadyne.com for full instructions.

- Remove center console side trim attachment screw on right side.
- Remove two right side center console side trim panels.
- Remove center console side trim attachment screw on left side.
- Remove two left side center console side trim panels.
- Locate connector H33-1, on the console floor to the left of the ignition switch. Switch ignition to “ON”, and verify there is 12V coming from pins 3 (12V+) & 4 (Gnd). If not, ensure there is a 30A fuse in spot 10 of the dash fuse panel. Turn vehicle off & remove key.
- Route cable through corresponding hole in armrest, down to floor, across floor of center console, to H33-1.
- Disconnect H33-1, and insert wires into connector. Pin 3 = yellow, and pin 4 = black.
Reconnect H33-1.
- Switch ignition to “ON”, and verify there is 12V coming from the powerport, or plug in a cigarette lighter to verify function.
- Plug thin wire to green light on white plastic shroud & install shroud (with light attached) to hole. Install metal powerport to plastic shroud. It is keyed & will only go in one way.
- Secure cable using included cable ties so it does not wander. ⚠️ Pay special attention to ensure cable will not interfere with operation of parking brake.
- Reassemble vehicle panels.